

PRE-ENGINEERED ROOF TRUSSES
DESIGNED BY ENGINEER

EXTERIOR
ROOF SHEATHING

AIR SPACE ROOF
VENT UNIT

INSULATION DESIGNED BY OTHERS

PROPER VENT AND TIE DOWN
MECHANICALLY TO CONCRETE CORE

OPTIONAL 2" EPS W/ 1/2"
PLYWOOD PRE-DRILL HOLE &
ATTACH W/ 3" SCREWS

WOOD
NAILER

FASCIA
BOARD

3/8" SOFFIT W/VENTING
2" CONTINUOUS VENT STRIPS

1X6 FRIEZE BOARD
(OPTIONAL)

VERTICAL REBAR
AS SPECIFIED BY
ENGINEER

GREENBLOCK
(ALL COURSES)

FINISH

GYPSUM BOARD CEILING

2X10 PRESSURE TREATED
PLATE W/SILL SEAL

TOP CONTINUOUS REBAR
AS SPECIFIED BY ENGINEER

ANCHOR BOLTS
ENGINEER SPECIFIED

MIN (1/2") GYPSUM BOARD

6"

Since 1967
GREENBLOCK[®]
Insulated Concrete Forms

Greenblock Worldwide Corporation
759 S. Federal Highway, Suite 213
Stuart, Florida 34994
Phone: 772-223-8045
Fax: 772-334-5554
Toll Free: 1-800-216-1820

www.Greenblock.com

6" CORE TYPICAL TRUSS CONNECTION
WITHOUT HURRICANE/TORNADO STRAPPING

REVISED DATE:	DRAWN BY: CAI
DATE: SEP 1, 2009	SCALE: 1-1/2" = 1'-0"
DETAIL NUMBER	GB-161

DISCLAIMER NOTICE: SPECIFIC INFORMATION FOR COMPLIANCE WITH LOCAL CODES, CONSTRUCTION PRACTICES AND REQUIREMENTS IS THE RESPONSIBILITY OF THE DESIGNER REGARDLESS OF DETAILS SHOWN IN DRAWING. GREENBLOCK WORLDWIDE CORPORATION RESERVES THE RIGHT TO CHANGE THE INFORMATION SHOWN WITHOUT NOTICE.